

# Sicam Falco AL520S Tyre Changer with Technofollower



GARAGE EQUIPMENT  
since 1922



Part No.: AL/FALCO520/TF

*See overleaf for  
more information*

- ▶ Technofollower to assist with low profile & run-flat tyres
- ▶ Tilting column for improved accessibility
- ▶ Extended clamping jaws for improved operation
- ▶ Pneumatic operated bead breaker
- ▶ Single speed, bidirectional turntable
- ▶ Ideal tyre changer for low volume workshops

# Sicam Falco AL520S Tyre Changer with Technofollower



GARAGE EQUIPMENT  
since 1922

## ► About the Falco AL520S

The Sicam Falco AL 520 S offers excellent performance with the reassurance of Italian manufacturing. With a clamping capacity of 23" together with a Technofollower, the AL 520 S provides the capacity to handle low profile and run-flat tyres with ease.

The Technofollower is a multi function pneumatic Assist Arm that enables the operator to:

- Apply pressure to the wheel and tyre when clamping to prevent tyre pinch
- Create space between the bead and rim when inserting the tyre lever
- Maintain the tyre bead below the rim and maintain this pressure whilst following the wheel rotation
- Reduce operator effort and minimises the risk of tyre slip and rip during the tyre to rim mounting process
- Deal with low profile and run-flat tyres with limited side-wall flex

Supplied with tyre lever and lubricant brush.  
Manufactured in Italy.

## ► Technical Specifications

External clamping.....	10" – 20"
Internal clamping.....	12" – 23"
Rim width.....	3" – 11"
Max. wheel diameter.....	1000mm
Bead breaker range.....	65 – 300mm
Air connection.....	8 – 10 bar
Rotation speed.....	7.5 rpm
Dimensions max. (HxDxW).....	1860 x 1660 x 1200mm

## ► Ordering Information

Sicam Falco AL5250S Tyre Changer 1ph with Technofollower.....AL/FALCO520/TF

## Issue No.: AL/FALCO520/TF

Tecalemit Garage Equipment Co Ltd  
Eagle Road, Langage Business Park,  
Plymouth, United Kingdom PL7 5JY

Sales: 00 44 (0) 1752 219 111  
Service: 00 44 (0) 1752 219 100  
Fax: 00 44 (0) 1752 219 128  
Email: sales@tecalemmit.co.uk  
Web: www.tecalemmit.co.uk



All information in this document is correct at time of publication. Tecalemit reserves the right to amend and alter specifications without prior notice. Please confirm any critical requirements with your supplier at time of ordering.