



**EXCLUSIVE
DISTRIBUTOR
FOR AUSTRALIA**



Heavy Vehicle Hoists



Finkbeiner - Your Wireless Choice



- Wireless communication via radio control, not Bluetooth.
- Power supply by deep cycle batteries, maintenance-free.
- Easy battery charging with only one power source per lift set.
- Operation during charging, allowing for full battery standby.
- Wireless remote control with LCD display, for operation of up to 8 columns.



SPECIFICATIONS: EHB 908 V11DC WIRELESS

Model / capacity	Mobile column EHB908V11DC wireless: Capacity 8.5 t
Wheel Forks	Adjustable wheel forks to suit wheel sizes 155R13 - 13R 22.5, Ø 550 - 1140 mm. Length of fork is 385 mm and suitable for super singles
Lifting stroke	1750 mm (effective)
Operation	Up / Down. Fast / Slow speed. Operation modes: All / Single / Pair / Group. Integrated control panel with LCD screen display. Permanent memory of the configuration
Display	Large display of 116 x 57 mm on each column. Display shows active columns, position, operation mode., lifting height, battery capacity and radio communication signal quality
Control	Proportional valves for smooth control without any increments or abrupt speed variations. Wireless communication via industrial safety radio control. Control voltage 230V AC..
Drive	Electro-hydraulic. DC motor, 2.2 KW. hydraulic cylinder, self-lubricating and maintenance-free
Power source	Batteries, total 230 V, 80 Ah, per column, deep cycle, maintenance-free. Number of lift cycles is approx. 20 with full load
Battery charging	Simple and quick charging of up to 4 columns via one single 230 V supply within 10 minutes. Charging cable included. Lift can be charged during operation allowing full battery standby. Time to charge flat battery is approx. 8 hours
Safety features	Double load securing with hydraulic and mechanical locks, hydraulic pressure relief valve preventing overload. Main switch is lockable with emergency stop
Mobility	Spring-loaded wheel jack at rear of each column. Fron wheels are fixed
Dimensions	1200 x 1165 x 2255 mm (l x w x h) Low front leg height of 100 mm for vehicles with minimum ground clearance
Weight	540 kg
Protection	IP 54
Surface treatment	Powder coating
Safety standards	CE, EN 1493

Not just a hoist, but a commitment to workshop excellence.