# Wireless Heavy-duty Column Lift - 30 tonne





Part No.: SF/9490 See overleaf for more information

- → Lifting capacity of 7.5t per column
- Utilises wireless technology to safely lift a wide range of vehicles including Buses, Lorries and large vans
- → Permanently safe load & safety lock design
- → Electronic synchronisation of columns
- Operating controls on all columns

# Wireless Heavy-duty Column Lift - 30 tonne



### → About the SF/9490 range

The SF/9490 is a wireless 4-unit column lift powered by rechargeable 24v batteries. It benefits from an advanced synchronization system enabling the columns to rise and lower smoothly, even if the load is not the same for each column. A hydraulic pump powered by a 24v motor operates each column. For safety, a height limit switch automatically stops the lift once the maximum point is reached. The lifting will also stop when there is a difference of more than 50mm on any column. Each column also has a mechanical lock.

The SF/9490 displays the current lifting height, battery charge level, mode type, and other details. When the columns are in use, there are no cables or other trip hazards. Since the mobile columns are batterypowered, the columns can be easily relocated (when unladen) to numerous locations in the workshop. Each column has operation and emergency stop buttons for ease of use. As with all Tecalemit equipment, these lifts are fully certified. It also carries an IP54 rating meaning it is splash-proof.

## → Technical Specifications & Dimensions

Lifting Capacity	7.5t Per Column (30.0t Overall)
Max Lifting Height	1700mm
Voltage	24v
Motor Power	2.2kW
Column Dimensions	1300(L) x 1100(W) x 2300(H) mm
Fork Length	380mm
Fork Width	280 - 580mm
Weight	710kg (Per Column)
Lifting Time	120s
Battery Capacity	20 Up and Down cycles
Battery Charger	Single phase 220v

## Issue No.: SF/9490 Oct 2022

Tecalemit Garage Equipment Co Ltd Eagle Road, Langage Business Park, Plymouth, United Kingdom PL7 5JY

Sales: 00 44 (0) 1752 219 111 Service: 00 44 (0) 1752 219 100 Fax: 00 44 (0) 1752 219 128 sales@tecalemit.co.uk Email: Web: www.tecalemit.co.uk

All information in this document is correct at time of publication. Tecalemit reserves the right to amend and alter specifications without prior notice. Please confirm any critical requirements with your supplier at time of ordering.











