Sentinel 5.5t 2-Post Lift with Symmetric Arms

TECALEMIT
GARAGE EQUIPMENT
since 1922

Part No.: SF/9196
See overleaf for more information

- Automatic arm locking
- Low minimum lifting pad height of just 125mm
- Maintenance free lifting rams
- Cable synchronisation
- Symmetric arms extending to over 1800mm
- Single screw pads

Sentinel 5.5t 2-Post Lift with Symmetric Arms

GARAGE EQUIPMENT
since 1922

About the SF/9196

The SF/9196 baseless lift comes with symmetric arms for easy work access. These extendable, three-stage telescopic arms are ideal for vans and long wheel-based vehicles whilst also being adaptable for use with standard vehicles. The SF/9196 also comes in two height options - 5100mm as standard or 4200mm for workshops with height restrictions.





Technical Specifications & Dimensions

Pad height min	125mm
Lifting height	1965mm
Motor supply	3kW - 3ph
Drive through width	2600mm
Maximum load	5500kg
Maximum lifting/lowering time	35 secs
Weight	1080kg

Part Nos. & Ordering Information

5.5t Hydraulic 2 post lift with symmetric arms (standard height 5100mm - 3ph)	SF/9196
5.5t Hydraulic 2 post lift with symmetric arms (standard height 5100mm - 1ph)	SF/91956/1
5.5t Hydraulic 2 post lift with symmetric arms (lower height 4200mm - 3ph)	SF/9196/LH
5.5t Hydraulic 2 post lift with symmetric arms (lower height 4200mm - 1ph)	SF/9196/1/LH

Options & Accessories

High lift extensions 60mm (set of 4)	OA/50733
High lift extensions 100mm (set of 4)	OA/50734
High lift extensions 170mm (set of 4)	OA/50735
High lift extensions 250mm (set of 4)	OA/50736
"U" Chassis crutch adaptors (set of 4)	OA/60264
"V" Chassis crutch adaptors (set of 4)	OA/62556
Plates with pins (set of 4)	OA/62557

Issue No.: SF/9196 Aug 2023

Tecalemit Garage Equipment Co Ltd, Eagle Road, Langage Business Park, Plymouth, United Kingdom PL7 5JY

Sales: 00 44 (0) 1752 219 111
Service: 00 44 (0) 1752 219 100
Fax: 00 44 (0) 1752 219 128
Email: sales@tecalemit.co.uk
Web: www.tecalemit.co.uk

All information in this document is correct at time of publication. Tecalemit reserves the right to amend and alter specifications without prior notice. Please confirm any critical requirements with your supplier at time of ordering.