Class 1 & 2 Motorcycle MOT Package





Part No.: MOT/3000 See overleaf for more information

Comprised of the following:-

- → DE/9015 Motorcycle Brake Tester:
 - 1ph, wall-mounted display, bi-directional, automatic weighing, roller covers, infrared remote control
- → DE/7288 Headlamp Beam Tester, rail mounted, MOT approved
- → OA/50681 Motorcycle alignment bars and cords
- → Package includes installation and certification of equipment
- Free equipment layout planning service from Tecalemit

Class 1 & 2 Motorcycle MOT Package



→ About the DE/9015

- Clear LED display
- Flush fitting rollers
- Starting safety device
- Analogue display of brake force
- Automatic zero calibration point
- Approved by DVSA for MOT application
- Accurate, consistent and reliable results
- Easy to use with remote control and automatic calculations throughout the test
- Automatic built in 4 point weighting system for accurate calculations
- Digital display of maximum brake force, bike weight and retardation etc.
- Unique large wheel slip roller to better accommodate off-road tyres
- Epoxy corundum coated rollers
- Easy drive out mode
- Stop/start manual control button on display
- Manual emergency stop button built in on display
- Low speed rollers to avoid 'kick-out'
- Pedestal mounted display option available
- Roller covers to meet Health & Safety requirements

Power	1ph,	240v/	/50Hz, 25a
Roller length			300mm
Motor			2.2kW
Roller distance			400mm
Test speed			2.9Km/h
Roller diameter			206mm
Brake force range		(0 - 300 kgf
Slip roller diameter			80mm
Max. wheel load			750kg
Roller tester weight			80kg
Roller surface friction).9 dry	/ > 0.6 wet
Display dimensions	680	x 680	x 120mm
Wheel slip sensing			Autostop
Chassis dimensions	800	x 620	x 310mm

→ About the DE/7288

- DVSA approved for all classes of MOT testing
- Suitable for testing supplementary beams & fog lamps
- Easy to read display screen
- Simple alignment & set up
- Wheeled option available for general workshop use

Lens to headlamp lens focal le	ngth350mm (+/-150mm)
Distance of lens in the front of	the first rail110mm
Maximum headlamp height	1500mm
Tolerance on aiming height	+/- 10mm
Optical box size	250mm x 250mm x 610mm
Distance between rails	395mm
Rail recess dimension1	00 x 27mm (min) / 29mm (max)

→ Options & Upgrades

Pedestal for brake tester displa	ayOA/60028/2/RAL5002				
Motorcycle brake tester installa	ation boxOA/60031/2				
Beam tester upgrade to laser type					
and RS232 connectivity	DE/7588				

→ Accessories

Mini Plus Electronic decelerometer with	
triaxial measurement (motorcycle)	DE/9046
Class 1 & 2 MOT accessory & sign pack	OA/60415/1

Issue No.: MOT/3000 Jul 2022

Tecalemit Garage Equipment Co Ltd Eagle Road, Langage Business Park, Plymouth, United Kingdom PL7 5JY

Sales: 00 44 (0) 1752 219 111 Service: 00 44 (0) 1752 219 100 Fax: 00 44 (0) 1752 219 128 Email: sales@tecalemit.co.uk Web: www.tecalemit.co.uk

All information in this document is correct at time of publication.
Tecalemit reserves the right to amend and alter specifications without prior notice. Please confirm any critical requirements with your supplier at time of ordering.











