Laser 4-Wheel Alignment System & Wall Rack





Part No.: GTR/420/W See overleaf for more information

- Highly accurate and easy to use
- Suitable for car wheel rim sizes up to 23"
- Compact wall mounted storage of equipment
- → On-rack recharging of lasers
- Includes pedal applicator and steering wheel clamp
- → Measures front & rear toe, total toe, set-back and rear axle thrust line

Laser 4-Wheel Alignment System & Wall Rack



GARAGE EQUIPMENT since 1922

→ Part Nos. & Ordering Information

4 Wheel laser alignment system......GTR/420/W

→ Options & Accessories

Extension kit allows sy<mark>stem</mark> to be used with 4x4 & Light Commercial Vehicles.....LA/XLKIT

→ Camber Caster Gauge with Digital Turn Disc

- Built in digital turn disc for caster swing measurement
- Simultaneous dual axis measurements
- Plus or minus 45° measurement
- 0.1 degree resolution
- Auto power off
- Magnetic adaptor for easy hub mounting

Camber caster gauge with digital turn disc.....LA/CTD

→ About the GTR/420/W

- Unique wheel clamping system
- Built and designed in the UK
- Precision engineered components
- High resolution class B laser
- Laser levelling
- Easy quick set up
- · Simple to use
- Suitable for wheel sizes from 12" 23"
- Low clearance measuring heads to clear front spoilers
- Measurement of:
 - Front & rear wheel toe
 - Total toe
 - Set back
 - Camber, Caster & SAI*
 - Rear wheel thrust line
- Wall mounted storage unit
- Built-in battery charger
- Includes pedal applicator & steering wheel clamp
- Includes graduated stainless steel turning plates
- LCV option available



Issue No.: GTR/420/W Dec 2023

Tecalemit Garage Equipment Co Ltd, Eagle Road, Langage Business Park, Plymouth, United Kingdom PL7 5JY

Sales: 00 44 (0) 1752 219 111
Service: 00 44 (0) 1752 219 100
Fax: 00 44 (0) 1752 219 128
Email: sales@tecalemit.co.uk
Web: www.tecalemit.co.uk

All information in this document is correct at time of publication. Tecalemit reserves the right to amend and alter specifications without prior notice. Please confirm any critical requirements with your supplier at time of ordering.













^{*} Requires optional camber caster gauge