Commercial Vehicle Hydraulic Play Detector













- Suitable for testing HGV and PSV Vehicles
- → Electro-hydraulic operation
- → 16 tonne axle capacity (8000kg per wheel)
- → Compact control box
- → Movements in 4 directions
- → Robust hand held control / lamp
- → Installation into floor recess
- → Suitable for use in Test Lanes

Commercial Vehicle Hydraulic Play Detector



→ About the DE/7353

The DE/7353 hydraulic play detector is designed for statutory testing of Heavy Goods Vehicles (HGV) and Public Service Vehicles (PSV) in accordance with the MOT test. The play detector checks for play and wear in the suspension and steering parts.

The system consists of two platforms and a control unit with a control lamp. The vehicle is placed with one axle on the platforms. The platforms will pull the wheels along, so the wheel will move relative to the vehicle body; this reveals play and wear in the suspension and steering components.

You control the platforms using a handheld control lamp. This means that you can move the platforms while you are underneath the vehicle to inspect it. A bracket is supplied for safe storage of the control lamp.


It is essential to contact Tecalemit to arrange a site survey before ordering and before any civil works, ready for installation of the embedded frame.

→ Technical Specifications & Dimensions

Maximum drive over weight	20000 kg per axle
	10000 kg per wheel
Maximum test weight	8000 kg per wheel
Longitudinal/transversal movement	100 mm
Movement speed	40 mm/s
Power	
Voltage	3ph, 400 V, 50 Hz
Hand held control cable length	6.5 m
Working pressure	215 bar
Play detector plate dimensions	
950 x 800 x 217mm (L x W x H)	
Weight	300 kg each
Hydraulic control unit dimensions	
360 x 300 x	x 875 mm (D x W x H)
Weight	36 kg
-	

→ Part Nos. & Ordering Information

Commercial Vehicle Hydraulic Play Detector.....DE/7353



Issue No.: DE/7353 May 2021

Tecalemit Garage Equipment Co Ltd Eagle Road, Langage Business Park, Plymouth, United Kingdom PL7 5JY

Sales: 00 44 (0) 1752 219 111
Service: 00 44 (0) 1752 219 100
Fax: 00 44 (0) 1752 219 128
Email: sales@tecalemit.co.uk
Web: www.tecalemit.co.uk

All information in this document is correct at time of publication.
Tecalemit reserves the right to amend and alter specifications without prior notice. Please confirm any critical requirements with your supplier at time of ordering.











